

## ESSENTIAL SANDSTONE SEALER MATT (Dry/Invisible Finish)

**5L** **25L** SKU: SC4U\_ERS\_SAM05 / SC4U\_ERS\_SAM25

### DESCRIPTION

#### Professional performance sandstone sealer

SC4U ESSENTIAL SANDSTONE SEALER MATT is a high performance stone sealer formulated especially for external sandstone surfaces. Also suitable for other porous natural stone such as limestone and slate. ESSENTIAL SANDSTONE SEALER MATT provides excellent water repellency and long lasting protection. Once sealed the attractive dry 'invisible' finish helps to protect against dirt, efflorescence, moss and algae growth. It also creates a self-cleaning surface tension that helps to reduce the need for regular maintenance.

### DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Before application the surface must be completely clean and dry. Application methods include a low pressure sprayer, roller, natural fibre brush or sponge.
- Apply **Essential Sandstone Sealer Matt**, to saturation. Two coats "wet on wet" are needed to ensure complete coverage. **DO NOT DILUTE.**
- Apply a second lighter application approximately 45-60 minutes later. After application it is important that the stone surface is kept completely dry throughout the curing process, which can be up to 72 hours. Any moisture or water left on the surface may result in the sealer drying inconsistently, possibly creating unsightly white patches.

**Please Note: Essential Sandstone Sealer Matt** may cause a change of appearance/colour on some stone types. Surfaces which are not to be sealed should be protected with masking material. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED, CERAMIC/GLAZED, DENSE OR NON-POROUS SURFACES.**

### MAINTENANCE

Clean sealed areas with a mild, ph neutral cleaner or a very low concentration of our outdoor cleaner range. Do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

### COVERAGE

Average 4-6sq metres per litre. Coverage will vary depending on surface porosity.

### USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats	Sponge/Brush/ Sprayer/Roller	Undiluted

### PRECAUTIONS

#### KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.

P102: Keep out of reach of children.  
P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear protective gloves.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.  
P332+313: If skin irritation occurs: Get medical advice.  
P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from [www.stonecare4u.co.uk](http://www.stonecare4u.co.uk).

